

Wall mounted unit

FTXC-C / RXC-C

BLUEEVOLUTION sensira



Energy saving during standby mode



Online controller via app

Wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily with any interior décor and is easier to clean
- › Online controller (optional)

- › Seasonal efficiency values up to A++ in cooling
- › Bluevolution range: lower environmental impact

FTXC-C / RXC-C



FTXC-C




RXC20-35C

Efficiency data		FTXC + RXC	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	71C + 71C
Cooling capacity	Min./Max.	kW	1.3 /3.0		1.3 /4.0	1.4 /6.2	1.8 /7.0	2.3 /7.3
Heating capacity	Min./Max.	kW	1.30 /4.00		1.30 /4.80	1.36 /6.60	1.48 /8.00	2.30 /9.00
Space cooling	Energy efficiency class		A++					A
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.96
	SEER			6.89	6.84	6.87	6.45	6.40
	η _{s,c}		%	-				
	Annual energy consumption	kWh/a	106	132	175	276	340	459
Space heating (Average climate)	Energy efficiency class		A+					A
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	6.35
	SCOP/A			4.40	4.45	4.28	4.42	4.24
	η _{s,h}		%	-				
	Annual energy consumption	kWh/a	594	700	732	1,236	1,354	2,334

Indoor unit		FTXC	20C	25C	35C	50C	60C	71C		
Dimensions	Unit	HeightxWidthxDepth	mm			288 x770 x234		297 x990 x273		
Weight	Unit		kg		9.00		9.50			
Air filter	Type		Removable / washable					13.0		
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m ³ /min	5.4 /6.5 /9 /10.8		7.4 /8.2 /10 /12.2		10.2 /13.6 /16 /20.4	
Sound power level	Cooling			dBA	54		55		57	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	20 /26 /38		21 /26 /39		29 /33 /45	
Control systems	Infrared remote control				ARC486A2					
	Wired remote control				-					

Outdoor unit		RXC	20C	25C	35C	50C	60C	71C		
Dimensions	Unit	HeightxWidthxDepth	mm			550 x658 x273		615 x845 x300		
Weight	Unit		kg		24.0		26.0			
Sound power level	Cooling			dBA	58		60			
Sound pressure level	Cooling	High		dBA	45		46			
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10 ~46		-10 ~46			
	Heating	Ambient	Min.~Max.	°CWB	-15 ~18					
Refrigerant	Type				R-32					
	GWP				675.0					
Piping connections	Charge			kg/CO ₂ Eq	0.550 /0.371		0.750 /0.506		1.00 /0.675	
	Liquid	OD		mm	6.4					
	Gas	OD		mm	9.52		12.7			
	Piping length	OU - IU	Max.	m	20		30			
	Additional refrigerant charge	System	Chargeless	m	8					
Power supply	Level	IU - OU	Max. difference	kg/m	0,017 (for piping length exceeding 7.5m)					
	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240					
Current - 50Hz	Maximum fuse amps (MFA)			A	16					

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-045

12/2020



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.